

# Week 9: *Cleaning Data*

🏛️ EMSE 4575: Exploratory Data Analysis


👤 John Paul Helveston

📅 March 10, 2021

# Quiz 3

Link is on the [schedule](#)

10:00



# Waffles and Animations

## Waffles

The bug:

```
install.packages("waffle")
```

The fix:

```
install.packages("waffle",  
  repos = "https://cinc.rud.is")
```

## Animation

The bug:

```
animate(anim_plot)
```

The fix:

```
install.packages('magick')  
animate(anim_plot,  
  renderer = magick_renderer())
```

## *Tip of the week*

Copy-paste magic with [datapasta](#)

**Useful for "small data":** e.g., [U.S. State Abbreviations](#)

# Today's data

## "Clean" data

```
wildlife_impacts <- read_csv(here::here('data', 'wildlife_impacts.csv'))  
milk_production  <- read_csv(here::here('data', 'milk_production.csv'))  
msleep           <- read_csv(here::here('data', 'msleep.csv'))
```

## "Messy" data

```
wind             <- read_excel(here::here('data', 'US_State_Wind_Energy_Facts_2018.xlsx'))  
hot_dogs         <- read_excel(here::here('data', 'hot_dog_winners.xlsx'))
```

## Plus two new packages:

```
# For manipulating dates  
install.packages('lubridate')  
  
# For cleaning column names  
install.packages('janitor')
```

# Week 9: *Cleaning Data*

1. Merging datasets with joins
2. Are your variables the right *type*?
3. Are your variables the right *name*?

**BREAK**

4. Re-coding variables
5. Dates
6. Dealing with messy Excel files

# Week 9: *Cleaning Data*

1. Merging datasets with joins
2. Are your variables the right *type*?
3. Are your variables the right *name*?


BREAK

4. Re-coding variables
5. Dates
6. Dealing with messy Excel files



## A state breakdown of who's skipping medications because they're too costly

Across the U.S., 28% of consumers ages 19 to 64 say they have not taken their prescription drugs as their health care provider has prescribed them because of cost, [according to AARP research](#). Here's a look at the percentage by state of residents who say they stopped taking medication due to cost.



Made with 

# What's wrong with this map?

## Likely culprit: Merging two columns

```
head(names)
```

```
#>   state_name  
#> 1   Alabama  
#> 2   Alaska  
#> 3   Arizona  
#> 4   Arkansas  
#> 5 California  
#> 6   Colorado
```

```
head(abbs)
```

```
#>   state_abb  
#> 1         AK  
#> 2         AL  
#> 3         AR  
#> 4         AZ  
#> 5         CA  
#> 6         CO
```

```
result <- bind_cols(names, abbs)  
head(result)
```

```
#>   state_name state_abb  
#> 1   Alabama         AK  
#> 2   Alaska         AL  
#> 3   Arizona         AR  
#> 4   Arkansas        AZ  
#> 5 California        CA  
#> 6   Colorado        CO
```

# Joins

1. `inner_join()`
2. `left_join()` / `right_join()`
3. `full_join()`

Example: `band_members` & `band_instruments`

`band_members`

```
#> # A tibble: 3 x 2
#>   name band
#>   <chr> <chr>
#> 1 Mick  Stones
#> 2 John  Beatles
#> 3 Paul  Beatles
```

`band_instruments`


```
#> # A tibble: 3 x 2
#>   name plays
#>   <chr> <chr>
#> 1 John  guitar
#> 2 Paul  bass
#> 3 Keith guitar
```

# inner\_join()

```
band_members %>%  
  inner_join(band_instruments)
```

```
#> # A tibble: 2 x 3  
#>   name band plays  
#>   <chr> <chr> <chr>  
#> 1 John Beatles guitar  
#> 2 Paul Beatles bass
```

inner\_join(x, y)




# full\_join()

```
band_members %>%  
  full_join(band_instruments)
```

```
#> # A tibble: 4 x 3  
#>   name  band  plays  
#>   <chr> <chr> <chr>  
#> 1 Mick  Stones <NA>  
#> 2 John  Beatles guitar  
#> 3 Paul  Beatles bass  
#> 4 Keith <NA>   guitar
```

full\_join(x, y)




# left\_join()

```
band_members %>%  
  left_join(band_instruments)
```

```
#> # A tibble: 3 x 3  
#>   name  band  plays  
#>   <chr> <chr> <chr>  
#> 1 Mick  Stones <NA>  
#> 2 John  Beatles guitar  
#> 3 Paul  Beatles bass
```

left\_join(x, y)




# right\_join()

```
band_members %>%  
  right_join(band_instruments)
```

```
#> # A tibble: 3 x 3  
#>   name band plays  
#>   <chr> <chr> <chr>  
#> 1 John Beatles guitar  
#> 2 Paul Beatles bass  
#> 3 Keith <NA> guitar
```

right\_join(x, y)



# Specify the joining variable name

```
band_members %>%  
  left_join(band_instruments)
```

```
#> Joining, by = "name"
```

```
#> # A tibble: 3 x 3  
#>   name band    plays  
#>   <chr> <chr>  <chr>  
#> 1 Mick  Stones <NA>  
#> 2 John  Beatles guitar  
#> 3 Paul  Beatles bass
```

```
band_members %>%  
  left_join(band_instruments,  
            by = 'name')
```

```
#> # A tibble: 3 x 3  
#>   name band    plays  
#>   <chr> <chr>  <chr>  
#> 1 Mick  Stones <NA>  
#> 2 John  Beatles guitar  
#> 3 Paul  Beatles bass
```



# Specify the joining variable name

If the names differ, use `by = c("left_name" = "joining_name")`

```
band_members
```

```
#> # A tibble: 3 x 2
#>   name band
#>   <chr> <chr>
#> 1 Mick  Stones
#> 2 John  Beatles
#> 3 Paul  Beatles
```

```
band_instruments2
```

```
#> # A tibble: 3 x 2
#>   artist plays
#>   <chr>  <chr>
#> 1 John   guitar
#> 2 Paul   bass
#> 3 Keith  guitar
```

```
band_members %>%
  left_join(band_instruments2,
            by = c("name" = "artist"))
```

```
#> # A tibble: 3 x 3
#>   name band plays
#>   <chr> <chr> <chr>
#> 1 Mick  Stones <NA>
#> 2 John  Beatles guitar
#> 3 Paul  Beatles bass
```

# Specify the joining variable name

Or just rename the joining variable in a pipe

```
band_members
```

```
#> # A tibble: 3 x 2  
#>   name band  
#>   <chr> <chr>  
#> 1 Mick  Stones  
#> 2 John  Beatles  
#> 3 Paul  Beatles
```

```
band_instruments2
```

```
#> # A tibble: 3 x 2  
#>   artist plays  
#>   <chr>   <chr>  
#> 1 John   guitar  
#> 2 Paul   bass  
#> 3 Keith  guitar
```

```
band_members %>%  
  rename(artist = name) %>%  
  left_join(band_instruments2,  
            by = "artist")
```

```
#> # A tibble: 3 x 3  
#>   artist band    plays  
#>   <chr>   <chr>   <chr>  
#> 1 Mick   Stones  <NA>  
#> 2 John   Beatles guitar  
#> 3 Paul   Beatles bass
```



# Week 9: *Cleaning Data*

1. Merging datasets with joins

2. *Are your variables the right type?*

3. *Are your variables the right name?*

BREAK

4. Re-coding variables

5. Dates

6. Dealing with messy Excel files

# Using the `col_types` argument

- You can change the column type when reading in data
- Different syntax for `readxl::read_excel()` and `readr::read_csv()`

# readxl::read\_excel()

`col_types` must be a vector describing each column type

```
wind <- read_excel(here::here(
  'data', 'US_State_Wind_Energy_Facts_2018.xlsx'))
glimpse(wind)
```

```
#> Rows: 50
#> Columns: 7
#> $ Ranking <chr> "1.0", "2.0",
#> $ State <chr> "TEXAS", "OKLA
#> $ `Installed Capacity (MW)` <dbl> 23262, 7495, 7
#> $ `Equivalent Homes Powered` <chr> "6235000.0", "
#> $ `Total Investment ($ Millions)` <chr> "42000.0", "13
#> $ `Wind Projects Online` <dbl> 136, 45, 107,
#> $ `# of Wind Turbines` <chr> "12750.0", "37
```

# readxl::read\_excel()

`col_types` must be a vector describing each column type

```
columns <- c('numeric', 'text', rep('numeric', 5))  
columns
```

```
#> [1] "numeric" "text"      "numeric" "numeric" "numer
```

```
wind <- read_excel(here::here(  
  'data', 'US_State_Wind_Energy_Facts_2018.xlsx'),  
  col_types = columns)
```

```
glimpse(wind)
```

```
#> Rows: 50  
#> Columns: 7  
#> $ Ranking <dbl> 1, 2, 3, 4  
#> $ State <chr> "TEXAS", '  
#> $ `Installed Capacity (MW)` <dbl> 23262, 749  
#> $ `Equivalent Homes Powered` <dbl> 6235000, 2  
#> $ `Total Investment ($ Millions)` <dbl> 42000, 137  
#> $ `Wind Projects Online` <dbl> 136, 45, 1  
#> $ `# of Wind Turbines` <dbl> 12750, 371
```

How it is in Excel	How it will be in R	How to request in <code>col_types</code>
anything	non-existent	"skip"
empty	logical, but all NA	you cannot request this
boolean	logical	"logical"
numeric	numeric	"numeric"
datetime	POSIXct	"date"
text	character	"text"
anything	list	"list"

## readr::read\_csv()

`col_types` describes individual variables by name using `cols()`

```
milks <- read_csv(here::here(
  'data', 'milk_production.csv'),
  col_types = cols(year = col_character()))

glimpse(milks)
```

```
#> Rows: 2,400
#> Columns: 4
#> $ region      <chr> "Northeast", "Northeast", "N
#> $ state       <chr> "Maine", "New Hampshire", "\
#> $ year        <chr> "1970", "1970", "1970", "197
#> $ milk_produced <dbl> 6.1900e+08, 3.5600e+08, 1.97
```



# readr::read\_csv()

`col_types` describes individual variables by name using `cols()`

Type	<code>dplyr::glimpse()</code>	<code>readr::parse_*()</code>	<code>readr::col_*()</code>
Logical	<code>&lt;lgl&gt;</code>	<code>parse_logical()</code>	<code>col_logical()</code>
Numeric	<code>&lt;int&gt;</code> or <code>&lt;dbl&gt;</code>	<code>parse_number()</code>	<code>col_number()</code>
Character	<code>&lt;chr&gt;</code>	<code>parse_character()</code>	<code>col_character()</code>
Factor	<code>&lt;fct&gt;</code>	<code>parse_factor(levels)</code>	<code>col_factor(levels)</code>
Date	<code>&lt;date&gt;</code>	<code>parse_date(format)</code>	<code>col_date(format)</code>

# Other option: Edit types **after** reading in the data

```
wind <- read_excel(here::here('data', 'US_State_Wind_Energy_Facts_2018.xlsx'))
mutate(
  Ranking = as.numeric(Ranking),
  `Equivalent Homes Powered` = as.numeric(`Equivalent Homes Powered`),
  `Total Investment ($ Millions)` = as.numeric(`Total Investment ($ Millions)`),
  `# of Wind Turbines` = as.numeric(`# of Wind Turbines`)
)
glimpse(wind)
```

```
#> Rows: 50
#> Columns: 7
#> $ Ranking <dbl> 1
#> $ State <chr> "Maine"
#> $ `Installed Capacity (MW)` <dbl> 2
#> $ `Equivalent Homes Powered` <dbl> 6
#> $ `Total Investment ($ Millions)` <dbl> 4
#> $ `Wind Projects Online` <dbl> 1
#> $ `# of Wind Turbines` <dbl> 1
```

```
milk <- read_csv(here::here('data', 'milk_production.csv')) %>%
mutate(year = as.character(year))
glimpse(milk)
```

```
#> Rows: 2,400
#> Columns: 4
#> $ region <chr> "Northeast", "North
#> $ state <chr> "Maine", "New Hamp
#> $ year <chr> "1970", "1970", "19
#> $ milk_produced <dbl> 6.1900e+08, 3.5600e
```

# Week 9: *Cleaning Data*

1. Merging datasets with joins
2. Are your variables the right *type*?
3. **Are your variables the right *name*?**

BREAK

4. Re-coding variables
5. Dates
6. Dealing with messy Excel files

# Renaming made easy

```
janitor::clean_names()
```



```
wind <- read_excel(here::here(  
  'data', 'US_State_Wind_Energy_Facts_2018.xlsx'))  
  
glimpse(wind)
```

```
#> Rows: 50  
#> Columns: 7  
#> $ Ranking <chr> "1.0", "2.0",  
#> $ State <chr> "TEXAS", "OKLA  
#> $ `Installed Capacity (MW)` <dbl> 23262, 7495, 7  
#> $ `Equivalent Homes Powered` <chr> "6235000.0", "  
#> $ `Total Investment ($ Millions)` <chr> "42000.0", "13  
#> $ `Wind Projects Online` <dbl> 136, 45, 107,  
#> $ `# of Wind Turbines` <chr> "12750.0", "37
```

# Renaming made easy

```
janitor::clean_names()
```



```
library(janitor)
```

```
wind <- read_excel(here::here(  
  'data', 'US_State_Wind_Energy_Facts_2018.xlsx')) %>%  
  clean_names()
```

```
glimpse(wind)
```

```
#> Rows: 50  
#> Columns: 7  
#> $ ranking      <chr> "1.0", "2.0", "3.0",  
#> $ state        <chr> "TEXAS", "OKLAHOMA",  
#> $ installed_capacity_mw <dbl> 23262, 7495, 7312, 5  
#> $ equivalent_homes_powered <chr> "6235000.0", "226800  
#> $ total_investment_millions <chr> "42000.0", "13700.0"  
#> $ wind_projects_online <dbl> 136, 45, 107, 104, 3  
#> $ number_of_wind_turbines <chr> "12750.0", "3717.0",
```

# Renaming made easy

```
janitor::clean_names()
```



```
library(janitor)
```

```
wind <- read_excel(here::here(  
  'data', 'US_State_Wind_Energy_Facts_2018.xlsx')) %>%  
  clean_names(case = 'lower_camel')
```

```
glimpse(wind)
```

```
#> Rows: 50  
#> Columns: 7  
#> $ ranking      <chr> "1.0", "2.0", "3.0", "  
#> $ state        <chr> "TEXAS", "OKLAHOMA", "  
#> $ installedCapacityMw <dbl> 23262, 7495, 7312, 568  
#> $ equivalentHomesPowered <chr> "6235000.0", "2268000.  
#> $ totalInvestmentMillions <chr> "42000.0", "13700.0",  
#> $ windProjectsOnline <dbl> 136, 45, 107, 104, 35,  
#> $ numberOfWindTurbines <chr> "12750.0", "3717.0", "
```

# Renaming made easy

```
janitor::clean_names()
```



```
library(janitor)
```

```
wind <- read_excel(here::here(  
  'data', 'US_State_Wind_Energy_Facts_2018.xlsx')) %>%  
  clean_names(case = 'screaming_snake')
```

```
glimpse(wind)
```

```
#> Rows: 50  
#> Columns: 7  
#> $ RANKING <chr> "1.0", "2.0", "3.0",  
#> $ STATE <chr> "TEXAS", "OKLAHOMA",  
#> $ INSTALLED_CAPACITY_MW <dbl> 23262, 7495, 7312, 5  
#> $ EQUIVALENT_HOMES_POWERED <chr> "6235000.0", "226800  
#> $ TOTAL_INVESTMENT_MILLIONS <chr> "42000.0", "13700.0"  
#> $ WIND_PROJECTS_ONLINE <dbl> 136, 45, 107, 104, 3  
#> $ NUMBER_OF_WIND_TURBINES <chr> "12750.0", "3717.0",
```

# select(): more powerful than you probably thought

Example: data on sleeping patterns of different mammals

```
glimpse(msleep)
```

```
#> Rows: 83
#> Columns: 11
#> $ name      <chr> "Cheetah", "Owl monkey", "Mountai
#> $ genus     <chr> "Acinonyx", "Aotus", "Aplodontia
#> $ vore      <chr> "carni", "omni", "herbi", "omni"
#> $ order     <chr> "Carnivora", "Primates", "Rodent
#> $ conservation <chr> "lc", NA, "nt", "lc", "domesticat
#> $ sleep_total <dbl> 12.1, 17.0, 14.4, 14.9, 4.0, 14.4
#> $ sleep_rem  <dbl> NA, 1.8, 2.4, 2.3, 0.7, 2.2, 1.4
#> $ sleep_cycle <dbl> NA, NA, NA, 0.1333333, 0.6666667
#> $ awake     <dbl> 11.90, 7.00, 9.60, 9.10, 20.00, 9
#> $ brainwt   <dbl> NA, 0.01550, NA, 0.00029, 0.42300
#> $ bodywt    <dbl> 50.000, 0.480, 1.350, 0.019, 600
```



# select(): more powerful than you probably thought

Use `select()` to choose which columns to **keep**

```
msleep %>%  
  select(name:order, sleep_total:sleep_cycle) %>%  
  glimpse()
```

```
#> Rows: 83  
#> Columns: 7  
#> $ name      <chr> "Cheetah", "Owl monkey", "Mou  
#> $ genus     <chr> "Acinonyx", "Aotus", "Aplodor  
#> $ vore      <chr> "carni", "omni", "herbi", "on  
#> $ order     <chr> "Carnivora", "Primates", "Rod  
#> $ sleep_total <dbl> 12.1, 17.0, 14.4, 14.9, 4.0,  
#> $ sleep_rem  <dbl> NA, 1.8, 2.4, 2.3, 0.7, 2.2,  
#> $ sleep_cycle <dbl> NA, NA, NA, 0.1333333, 0.6666
```

Use `select()` to choose which columns to **drop**

```
msleep %>%  
  select(-(name:order)) %>%  
  glimpse()
```

```
#> Rows: 83  
#> Columns: 7  
#> $ conservation <chr> "lc", NA, "nt", "l  
#> $ sleep_total  <dbl> 12.1, 17.0, 14.4,  
#> $ sleep_rem    <dbl> NA, 1.8, 2.4, 2.3,  
#> $ sleep_cycle  <dbl> NA, NA, NA, 0.1333  
#> $ awake       <dbl> 11.90, 7.00, 9.60,  
#> $ brainwt     <dbl> NA, 0.01550, NA, 0  
#> $ bodywt      <dbl> 50.000, 0.480, 1.3
```

# Select columns based on **partial column names**

Select columns that start with "sleep":

```
msleep %>%  
  select(name, starts_with("sleep")) %>%  
  glimpse()
```

```
#> Rows: 83  
#> Columns: 4  
#> $ name      <chr> "Cheetah", "Owl monkey",  
#> $ sleep_total <dbl> 12.1, 17.0, 14.4, 14.9,  
#> $ sleep_rem   <dbl> NA, 1.8, 2.4, 2.3, 0.7,  
#> $ sleep_cycle <dbl> NA, NA, NA, 0.1333333, 0
```

Select columns that contain "eep" and end with "wt":

```
msleep %>%  
  select(contains("eep"), ends_with("wt")) %>%  
  glimpse()
```

```
#> Rows: 83  
#> Columns: 5  
#> $ sleep_total <dbl> 12.1, 17.0, 14.4, 14.9,  
#> $ sleep_rem   <dbl> NA, 1.8, 2.4, 2.3, 0.7,  
#> $ sleep_cycle <dbl> NA, NA, NA, 0.1333333, 0  
#> $ brainwt     <dbl> NA, 0.01550, NA, 0.00029  
#> $ bodywt      <dbl> 50.000, 0.480, 1.350, 0.
```

# Select columns based on their **data type**

Select only numeric columns:

```
msleep %>%  
  select_if(is.numeric) %>%  
  glimpse()
```

```
#> Rows: 83  
#> Columns: 6  
#> $ sleep_total <dbl> 12.1, 17.0, 14.4, 14.4  
#> $ sleep_rem <dbl> NA, 1.8, 2.4, 2.3, 0.0  
#> $ sleep_cycle <dbl> NA, NA, NA, 0.1333333  
#> $ awake <dbl> 11.90, 7.00, 9.60, 9.60  
#> $ brainwt <dbl> NA, 0.01550, NA, 0.00000  
#> $ bodywt <dbl> 50.000, 0.480, 1.350, 1.350
```

Select only character columns:

```
msleep %>%  
  select_if(is.character) %>%  
  glimpse()
```

```
#> Rows: 83  
#> Columns: 5  
#> $ name <chr> "Cheetah", "Owl monk  
#> $ genus <chr> "Acinonyx", "Aotus",  
#> $ vore <chr> "carni", "omni", "herb  
#> $ order <chr> "Carnivora", "Primat  
#> $ conservation <chr> "lc", NA, "nt", "lc"
```

# Use `select()` to **reorder** variables

```
msleep %>%  
  select(everything()) %>%  
  glimpse()
```

```
#> Rows: 83  
#> Columns: 11  
#> $ name      <chr> "Cheetah", "Owl mo  
#> $ genus     <chr> "Acinonyx", "Aotus  
#> $ vore      <chr> "carni", "omni", "  
#> $ order     <chr> "Carnivora", "Prim  
#> $ conservation <chr> "lc", NA, "nt", "l  
#> $ sleep_total <dbl> 12.1, 17.0, 14.4,  
#> $ sleep_rem  <dbl> NA, 1.8, 2.4, 2.3,  
#> $ sleep_cycle <dbl> NA, NA, NA, 0.1333  
#> $ awake     <dbl> 11.90, 7.00, 9.60,  
#> $ brainwt   <dbl> NA, 0.01550, NA, 0  
#> $ bodywt    <dbl> 50.000, 0.480, 1.3
```

```
msleep %>%  
  select(conservation, awake, everything()) %>%  
  glimpse()
```

```
#> Rows: 83  
#> Columns: 11  
#> $ conservation <chr> "lc", NA, "nt", "lc", "domes  
#> $ awake        <dbl> 11.90, 7.00, 9.60, 9.10, 20.  
#> $ name         <chr> "Cheetah", "Owl monkey", "Mo  
#> $ genus        <chr> "Acinonyx", "Aotus", "Aplod  
#> $ vore         <chr> "carni", "omni", "herbi", "c  
#> $ order        <chr> "Carnivora", "Primates", "Ro  
#> $ sleep_total  <dbl> 12.1, 17.0, 14.4, 14.9, 4.0,  
#> $ sleep_rem    <dbl> NA, 1.8, 2.4, 2.3, 0.7, 2.2,  
#> $ sleep_cycle  <dbl> NA, NA, NA, 0.1333333, 0.666  
#> $ awake       <dbl> NA, 0.01550, NA, 0.00029, 0.  
#> $ bodywt      <dbl> 50.000, 0.480, 1.350, 0.019,
```

# Use `select()` to **rename** variables

Use `rename()` to just change the name

```
msleep %>%  
  rename(  
    animal = name,  
    extinction_threat = conservation) %>%  
  glimpse()
```

```
#> Rows: 83  
#> Columns: 11  
#> $ animal      <chr> "Cheetah", "Owl mo  
#> $ genus       <chr> "Acinonyx", "Aotus  
#> $ vore        <chr> "carni", "omni", "  
#> $ order       <chr> "Carnivora", "Prim  
#> $ extinction_threat <chr> "lc", NA, "nt", "l  
#> $ sleep_total  <dbl> 12.1, 17.0, 14.4,  
#> $ sleep_rem    <dbl> NA, 1.8, 2.4, 2.3,  
#> $ sleep_cycle  <dbl> NA, NA, NA, 0.1333  
#> $ awake       <dbl> 11.90, 7.00, 9.60,  
#> $ brainwt     <dbl> NA, 0.01550, NA, 0  
#> $ bodywt      <dbl> 50.000, 0.480, 1.3
```

Use `select()` to change the name **and drop everything else**

```
msleep %>%  
  select(  
    animal = name,  
    extinction_threat = conservation) %>%  
  glimpse()
```

```
#> Rows: 83  
#> Columns: 2  
#> $ animal      <chr> "Cheetah", "Owl mo  
#> $ extinction_threat <chr> "lc", NA, "nt", "l
```

# Use `select()` to **rename** variables

Use `rename()` to just change the name

```
msleep %>%  
  rename(  
    animal = name,  
    extinction_threat = conservation) %>%  
  glimpse()
```

```
#> Rows: 83  
#> Columns: 11  
#> $ animal      <chr> "Cheetah", "Owl mo  
#> $ genus       <chr> "Acinonyx", "Aotus  
#> $vore         <chr> "carni", "omni", "  
#> $ order       <chr> "Carnivora", "Prim  
#> $ extinction_threat <chr> "lc", NA, "nt", "l  
#> $ sleep_total  <dbl> 12.1, 17.0, 14.4,  
#> $ sleep_rem    <dbl> NA, 1.8, 2.4, 2.3,  
#> $ sleep_cycle  <dbl> NA, NA, NA, 0.1333  
#> $ awake        <dbl> 11.90, 7.00, 9.60,  
#> $ brainwt      <dbl> NA, 0.01550, NA, 0  
#> $ bodywt       <dbl> 50.000, 0.480, 1.3
```

Use `select()` + `everything()` to change names **and keep everything else**

```
msleep %>%  
  select(  
    animal = name,  
    extinction_threat = conservation,  
    everything()) %>%  
  glimpse()
```

```
#> Rows: 83  
#> Columns: 11  
#> $ animal      <chr> "Cheetah", "Owl mo  
#> $ extinction_threat <chr> "lc", NA, "nt", "l  
#> $ genus       <chr> "Acinonyx", "Aotus  
#> $vore         <chr> "carni", "omni", "  
#> $ order       <chr> "Carnivora", "Prim  
#> $ sleep_total  <dbl> 12.1, 17.0, 14.4,  
#> $ sleep_rem    <dbl> NA, 1.8, 2.4, 2.3,  
#> $ sleep_cycle  <dbl> NA, NA, NA, 0.1333  
#> $ awake        <dbl> 11.90, 7.00, 9.60,  
#> $ bodywt       <dbl> 50.000, 0.480, 1.3
```

# Your turn

Read in the `hot_dog_winners.xlsx` file and adjust the variable names and types to the following:

```
#> Rows: 42
#> Columns: 7
#> $ year          <dbl> 1980,
#> $ competitor.mens <chr> "Paul
#> $ competitor.womens <chr> NA, NA
#> $ dogs_eaten.mens <dbl> 9.10,
#> $ dogs_eaten.womens <dbl> NA, NA
#> $ country.mens <chr> "Unite
#> $ country.womens <chr> NA, NA
```

15:00

	A	B	C	D	E	F	G
1	Year	Mens	Dogs eaten	Country	Womens	Dogs eaten	Country
2	1980	Paul Siederman & Joe Baldini	9.1	United States			
3	1981	Thomas DeBerry	11	United States			
4	1982	Steven Abrams	11	United States			
5	1983	Luis Llamas	19.5	Mexico			
6	1984	Birgit Felden	9.5	Germany			
7	1985	Oscar Rodriguez	11.75	United States			
8	1986	Mark Heller	15.5	United States			
9	1987	Don Wolfman	12	United States			
10	1988	Jay Green	14	United States			
11	1989	Jay Green	13	United States			
12	1990	Mike DeVito	16	United States			
13	1991	Frank Dellarosa	21.5*	United States			
14	1992	Frank Dellarosa	19	United States			
15	1993	Mike DeVito	17	United States			
16	1994	Mike DeVito	20	United States			
17	1995	Edward Krachie	19.5	United States			
18	1996	Edward Krachie	22.25*	United States			
19	1997	Hirofumi Nakajima	24.5*	Japan			
20	1998	Hirofumi Nakajima	19	Japan			
21	1999	Steve Keiner	20.25	United States			
22	2000	Kazutoyo Arai	25.13*	Japan			
23	2001	Takeru Kobayashi	50*	Japan			
24	2002	Takeru Kobayashi	50.5*	Japan			
25	2003	Takeru Kobayashi	44.5	Japan			
26	2004	Takeru Kobayashi	53.5*	Japan			
27	2005	Takeru Kobayashi	49	Japan			
28	2006	Takeru Kobayashi	53.75*	Japan			
29	2007	Joey Chestnut	66*	United States			
30	2008	Joey Chestnut	59	United States			
31	2009	Joey Chestnut	68*	United States			
32	2010	Joey Chestnut	54	United States			
33	2011	Joey Chestnut	62	United States	Sonya Thomas	40*	United States
34	2012	Joey Chestnut	68	United States	Sonya Thomas	45*	United States
35	2013	Joey Chestnut	69*	United States	Sonya Thomas	36.75	United States
36	2014	Joey Chestnut	61	United States	Miki Sudo	34	United States
37	2015	Matt Stonie	62	United States	Miki Sudo	38	United States
38	2016	Joey Chestnut	70*	United States	Miki Sudo	38.5	United States
39	2017	Joey Chestnut	72*	United States	Miki Sudo	41	United States
40	2018	Joey Chestnut	74*	United States	Miki Sudo	37	United States
41	2019	Joey Chestnut	71	United States	Miki Sudo	31	United States
42							
43	Notes:	* means new record					

# Break!

Stand up, Move around, Stretch!

05:00



# Week 9: *Cleaning Data*

1. Merging datasets with joins
2. Are your variables the right *type*?
3. Are your variables the right *name*?

BREAK

4. **Re-coding variables**
5. Dates
6. Dealing with messy Excel files

# Recoding with `ifelse()`

Example: Create a variable, `cost_high`, that is `TRUE` if the repair costs were greater than the median costs and `FALSE` otherwise.

```
wildlife_impacts1 <- wildlife_impacts %>%
  rename(cost = cost_repairs_infl_adj) %>%
  filter(!is.na(cost)) %>%
  mutate(
    cost_median = median(cost),
    cost_high = ifelse(cost > cost_median, TRUE, FALSE))

wildlife_impacts1 %>%
  select(cost, cost_median, cost_high) %>%
  head()
```

```
#> # A tibble: 6 x 3
#>   cost cost_median cost_high
#>   <dbl>     <dbl> <lgl>
#> 1  1000     26783 FALSE
#> 2   200     26783 FALSE
#> 3 10000     26783 FALSE
#> 4 100000     26783  TRUE
#> 5  20000     26783 FALSE
#> 6 487000     26783  TRUE
```

# Recoding with **nested** `ifelse()`

Create a variable, `season`, based on the `incident_month` variable.

```
wildlife_impacts2 <- wildlife_impacts %>%  
  mutate(season = ifelse(  
    incident_month %in% c(3, 4, 5), 'spring', ifelse(  
      incident_month %in% c(6, 7, 8), 'summer', ifelse(  
        incident_month %in% c(9, 10, 11), 'fall', 'winter'))  
  )  
  
wildlife_impacts2 %>%  
  distinct(incident_month, season) %>%  
  head()
```

```
#> # A tibble: 6 x 2  
#>   incident_month season  
#>   <dbl> <chr>  
#> 1         12 winter  
#> 2         11 fall  
#> 3         10 fall  
#> 4          9 fall  
#> 5          8 summer  
#> 6          7 summer
```

# Recoding with `case_when()`

Create a variable, `season`, based on the `incident_month` variable.

**Note:** If you don't include the final `TRUE ~ 'winter'` condition, you'll get `NA` for those cases.

```
wildlife_impacts2 <- wildlife_impacts %>%
  mutate(season = case_when(
    incident_month %in% c(3, 4, 5) ~ 'spring',
    incident_month %in% c(6, 7, 8) ~ 'summer',
    incident_month %in% c(9, 10, 11) ~ 'fall',
    TRUE ~ 'winter')
  )

wildlife_impacts2 %>%
  distinct(incident_month, season) %>%
  head()
```

```
#> # A tibble: 6 x 2
#>   incident_month season
#>   <dbl> <chr>
#> 1     12 winter
#> 2     11 fall
#> 3     10 fall
#> 4      9 fall
#> 5      8 summer
#> 6      7 summer
```

# Recoding with `case_when()` with `between()`

Create a variable, `season`, based on the `incident_month` variable.

```
wildlife_impacts2 <- wildlife_impacts %>%  
  mutate(season = case_when(  
    between(incident_month, 3, 5) ~ 'spring',  
    between(incident_month, 6, 8) ~ 'summer',  
    between(incident_month, 9, 11) ~ 'fall',  
    TRUE ~ 'winter')  
  )  
  
wildlife_impacts2 %>%  
  distinct(incident_month, season) %>%  
  head()
```

```
#> # A tibble: 6 x 2  
#>   incident_month season  
#>   <dbl> <chr>  
#> 1      12 winter  
#> 2      11 fall  
#> 3      10 fall  
#> 4       9 fall  
#> 5       8 summer  
#> 6       7 summer
```

# case\_when() is "cleaner" than ifelse()

Convert the `num_engs` variable into a word of the number.

## ifelse()

```
wildlife_impacts3 <- wildlife_impacts %>%  
  mutate(num_engs = ifelse(  
    num_engs == 1, 'one', ifelse(  
    num_engs == 2, 'two', ifelse(  
    num_engs == 3, 'three', ifelse(  
    num_engs == 4, 'four',  
    as.character(num_engs))))))  
)  
unique(wildlife_impacts3$num_engs)
```

```
#> [1] "two" NA "three" "four" "one"
```

## case\_when()

```
wildlife_impacts3 <- wildlife_impacts %>%  
  mutate(num_engs = case_when(  
    num_engs == 1 ~ 'one',  
    num_engs == 2 ~ 'two',  
    num_engs == 3 ~ 'three',  
    num_engs == 4 ~ 'four')  
)  
unique(wildlife_impacts3$num_engs)
```

```
#> [1] "two" NA "three" "four" "one"
```

# Break a single variable into two with `separate()`

```
tb_rates
```

```
#> # A tibble: 6 x 3  
#>   country    year rate  
#> * <chr>      <int> <chr>  
#> 1 Afghanistan 1999 745/19987071  
#> 2 Afghanistan 2000 2666/20595360  
#> 3 Brazil      1999 37737/172006362  
#> 4 Brazil      2000 80488/174504898  
#> 5 China       1999 212258/1272915272  
#> 6 China       2000 213766/1280428583
```

```
tb_rates %>%
```

```
separate(rate, into = c("cases", "population"))
```

```
#> # A tibble: 6 x 4  
#>   country    year cases  population  
#>   <chr>      <int> <chr>   <chr>  
#> 1 Afghanistan 1999 745     19987071  
#> 2 Afghanistan 2000 2666    20595360  
#> 3 Brazil      1999 37737   172006362  
#> 4 Brazil      2000 80488   174504898  
#> 5 China       1999 212258  1272915272  
#> 6 China       2000 213766  1280428583
```

# Break a single variable into two with `separate()`

```
tb_rates
```

```
#> # A tibble: 6 x 3  
#>   country    year rate  
#> * <chr>      <int> <chr>  
#> 1 Afghanistan 1999 745/19987071  
#> 2 Afghanistan 2000 2666/20595360  
#> 3 Brazil      1999 37737/172006362  
#> 4 Brazil      2000 80488/174504898  
#> 5 China       1999 212258/1272915272  
#> 6 China       2000 213766/1280428583
```

```
tb_rates %>%  
  separate(rate, into = c("cases", "population"),  
           sep = "/")
```

```
#> # A tibble: 6 x 4  
#>   country    year cases  population  
#>   <chr>      <int> <chr>   <chr>  
#> 1 Afghanistan 1999 745     19987071  
#> 2 Afghanistan 2000 2666    20595360  
#> 3 Brazil      1999 37737   172006362  
#> 4 Brazil      2000 80488   174504898  
#> 5 China       1999 212258  1272915272  
#> 6 China       2000 213766  1280428583
```



# Break a single variable into two with `separate()`

```
tb_rates
```

```
#> # A tibble: 6 x 3  
#>   country      year rate  
#> * <chr>      <int> <chr>  
#> 1 Afghanistan 1999 745/19987071  
#> 2 Afghanistan 2000 2666/20595360  
#> 3 Brazil       1999 37737/172006362  
#> 4 Brazil       2000 80488/174504898  
#> 5 China        1999 212258/1272915272  
#> 6 China        2000 213766/1280428583
```

```
tb_rates %>%  
  separate(rate, into = c("cases", "population"),  
           sep = "/",  
           convert = TRUE)
```

```
#> # A tibble: 6 x 4  
#>   country      year cases population  
#>   <chr>      <int> <int>      <int>  
#> 1 Afghanistan 1999     745    19987071  
#> 2 Afghanistan 2000    2666    20595360  
#> 3 Brazil       1999   37737   172006362  
#> 4 Brazil       2000   80488   174504898  
#> 5 China        1999  212258  1272915272  
#> 6 China        2000  213766  1280428583
```

# You can also break up a variable by an index

```
tb_rates
```

```
#> # A tibble: 6 x 3
#>   country    year rate
#> * <chr>      <int> <chr>
#> 1 Afghanistan 1999 745/19987071
#> 2 Afghanistan 2000 2666/20595360
#> 3 Brazil      1999 37737/172006362
#> 4 Brazil      2000 80488/174504898
#> 5 China       1999 212258/1272915272
#> 6 China       2000 213766/1280428583
```

```
tb_rates %>%
  separate(year, into = c("century", "year"),
            sep = 2)
```

```
#> # A tibble: 6 x 4
#>   country    century year    rate
#>   <chr>      <chr>   <chr> <chr>
#> 1 Afghanistan 19      99    745/19987071
#> 2 Afghanistan 20      00    2666/20595360
#> 3 Brazil      19      99    37737/172006362
#> 4 Brazil      20      00    80488/174504898
#> 5 China       19      99    212258/1272915272
#> 6 China       20      00    213766/1280428583
```

# unite(): The opposite of separate()

tb\_rates

```
#> # A tibble: 6 x 3
#>   country      year rate
#> * <chr>      <int> <chr>
#> 1 Afghanistan 1999 745/19987071
#> 2 Afghanistan 2000 2666/20595360
#> 3 Brazil       1999 37737/172006362
#> 4 Brazil       2000 80488/174504898
#> 5 China        1999 212258/1272915272
#> 6 China        2000 213766/1280428583
```

```
tb_rates %>%
  separate(year, into = c("century", "year"),
           sep = 2) %>%
  unite(year_new, century, year)
```

```
#> # A tibble: 6 x 3
#>   country      year_new rate
#>   <chr>      <chr>      <chr>
#> 1 Afghanistan 19_99      745/19987071
#> 2 Afghanistan 20_00      2666/20595360
#> 3 Brazil       19_99      37737/172006362
#> 4 Brazil       20_00      80488/174504898
#> 5 China        19_99      212258/1272915272
#> 6 China        20_00      213766/1280428583
```

# unite(): The opposite of separate()

tb\_rates

```
#> # A tibble: 6 x 3
#>   country      year rate
#> * <chr>      <int> <chr>
#> 1 Afghanistan 1999 745/19987071
#> 2 Afghanistan 2000 2666/20595360
#> 3 Brazil       1999 37737/172006362
#> 4 Brazil       2000 80488/174504898
#> 5 China        1999 212258/1272915272
#> 6 China        2000 213766/1280428583
```

```
tb_rates %>%
  separate(year, into = c("century", "year"),
           sep = 2) %>%
  unite(year_new, century, year,
        sep = "'")
```

```
#> # A tibble: 6 x 3
#>   country      year_new rate
#>   <chr>      <chr>   <chr>
#> 1 Afghanistan 1999     745/19987071
#> 2 Afghanistan 2000     2666/20595360
#> 3 Brazil       1999     37737/172006362
#> 4 Brazil       2000     80488/174504898
#> 5 China        1999     212258/1272915272
#> 6 China        2000     213766/1280428583
```


# Week 9: *Cleaning Data*

1. Merging datasets with joins
2. Are your variables the right *type*?
3. Are your variables the right *name*?


BREAK

4. Re-coding variables
5. **Dates**
6. Dealing with messy Excel files


What is your idea of a perfect date?



YYYY/MM/DD, other formats can be really confusing



You will die single.



# Create dates from strings - **order is the ONLY thing that matters!**

Year-Month-Day

```
ymd( '2020-02-26' )
```

```
#> [1] "2020-02-26"
```

# Create dates from strings - **order is the ONLY thing that matters!**

Year-Month-Day

```
ymd('2020-02-26')
```

```
#> [1] "2020-02-26"
```

```
ymd('2020 Feb 26')
```

```
#> [1] "2020-02-26"
```



# Create dates from strings - **order is the ONLY thing that matters!**

Year-Month-Day

```
ymd('2020-02-26')
```

```
#> [1] "2020-02-26"
```

```
ymd('2020 Feb 26')
```

```
#> [1] "2020-02-26"
```

```
ymd('2020 Feb. 26')
```

```
#> [1] "2020-02-26"
```

```
ymd('2020 february 26')
```

```
#> [1] "2020-02-26"
```

Month-Day-Year

```
mdy('February 26, 2020')
```

```
#> [1] "2020-02-26"
```

```
mdy('Feb. 26, 2020')
```

```
#> [1] "2020-02-26"
```

```
mdy('Feb 26 2020')
```

```
#> [1] "2020-02-26"
```

Day-Month-Year

```
dmy('26 February 2020')
```

```
#> [1] "2020-02-26"
```

```
dmy('26 Feb. 2020')
```

```
#> [1] "2020-02-26"
```

```
dmy('26 Feb, 2020')
```

```
#> [1] "2020-02-26"
```

Check out the `lubridate` **cheat sheet**

# Extracting information from dates

```
date <- today()  
date
```

```
#> [1] "2021-03-10"
```

```
# Get the year  
year(date)
```

```
#> [1] 2021
```

# Extracting information from dates

```
date <- today()
date
```

```
#> [1] "2021-03-10"
```

```
# Get the year
year(date)
```

```
#> [1] 2021
```

```
# Get the month
month(date)
```

```
#> [1] 3
```

```
# Get the month name
month(date, label = TRUE, abbr = FALSE)
```

```
#> [1] March
#> Levels: January < February < March < April < May < June
```

```
# Get the day
day(date)
```

```
#> [1] 10
```

```
# Get the weekday
wday(date)
```

```
#> [1] 4
```

```
# Get the weekday name
wday(date, label = TRUE, abbr = TRUE)
```

```
#> [1] Wed
#> Levels: Sun < Mon < Tue < Wed < Thu < Fri < Sat
```

# Quick practice

On what day of the week were you born?

```
wday("2020-02-26", label = TRUE)
```

```
#> [1] Wed  
#> Levels: Sun < Mon < Tue < Wed < Thu < Fri < Sat
```

# Modifying date elements

```
date <- today()  
date
```

```
#> [1] "2021-03-10"
```

```
# Change the year  
year(date) <- 2016  
date
```

```
#> [1] "2016-03-10"
```

```
# Change the day  
day(date) <- 30
```

```
date
```

```
#> [1] "2016-03-30"
```

# Quick practice

What do you think will happen if we do this?

```
date <- ymd("2021-02-28")  
day(date) <- 30
```

```
date
```

```
#> [1] "2021-03-02"
```

# Your turn

20:00

1) Use `case_when()` to modify the `phase_of_flight` variable in the `wildlife_impacts` data:

- The values `'approach'`, `'arrival'`, `'descent'`, and `'landing roll'` should be merged into a single value called `'arrival'`.
- The values `'climb'`, `'departure'`, and `'take-off run'` should be merged into a single value called `'departure'`.
- All other values should be called `'other'`.

Before:

```
unique(str_to_lower(wildlife_impacts$phase_of_flight))
```


```
#> [1] "climb" "landing roll" NA "approach"
```

After:

```
#> [1] "departure" "arrival" "other"
```

2) Use the `lubridate` package to create a new variable, `weekday_name`, from the `incident_date` variable in the `wildlife_impacts` data.

3) Use `weekday_name` and `phase_of_flight` to make this plot of "arrival" and "departure" impacts from **Mar. 2016**.





# Week 9: *Cleaning Data*

1. Merging datasets with joins
2. Are your variables the right *type*?
3. Are your variables the right *name*?

BREAK

4. Re-coding variables
5. Dates
6. **Dealing with messy Excel files**

# When columns are repeated

Example: Winners of Nathan's hot dog eating contest

## Stragies

### 1. Divide & conquer

### 2. Gather, separate, spread

	A	B	C	D	E	F	G
1	Year	Mens	Dogs eaten	Country	Womens	Dogs eaten	Country
2	1980	Paul Siederman & Joe Baldini	9.1	United States			
3	1981	Thomas DeBerry	11	United States			
4	1982	Steven Abrams	11	United States			
5	1983	Luis Llamas	19.5	Mexico			
6	1984	Birgit Felden	9.5	Germany			
7	1985	Oscar Rodriguez	11.75	United States			
8	1986	Mark Heller	15.5	United States			
9	1987	Don Wolfman	12	United States			
10	1988	Jay Green	14	United States			
11	1989	Jay Green	13	United States			
12	1990	Mike DeVito	16	United States			
13	1991	Frank Dellarosa	21.5*	United States			
14	1992	Frank Dellarosa	19	United States			
15	1993	Mike DeVito	17	United States			
16	1994	Mike DeVito	20	United States			
17	1995	Edward Krachie	19.5	United States			
18	1996	Edward Krachie	22.25*	United States			
19	1997	Hirofumi Nakajima	24.5*	Japan			
20	1998	Hirofumi Nakajima	19	Japan			
21	1999	Steve Keiner	20.25	United States			
22	2000	Kazutoyo Arai	25.13*	Japan			
23	2001	Takeru Kobayashi	50*	Japan			
24	2002	Takeru Kobayashi	50.5*	Japan			
25	2003	Takeru Kobayashi	44.5	Japan			
26	2004	Takeru Kobayashi	53.5*	Japan			
27	2005	Takeru Kobayashi	49	Japan			
28	2006	Takeru Kobayashi	53.75*	Japan			
29	2007	Joey Chestnut	66*	United States			
30	2008	Joey Chestnut	59	United States			
31	2009	Joey Chestnut	68*	United States			
32	2010	Joey Chestnut	54	United States			
33	2011	Joey Chestnut	62	United States	Sonya Thomas	40*	United States
34	2012	Joey Chestnut	68	United States	Sonya Thomas	45*	United States
35	2013	Joey Chestnut	69*	United States	Sonya Thomas	36.75	United States
36	2014	Joey Chestnut	61	United States	Miki Sudo	34	United States
37	2015	Matt Stonie	62	United States	Miki Sudo	38	United States
38	2016	Joey Chestnut	70*	United States	Miki Sudo	38.5	United States
39	2017	Joey Chestnut	72*	United States	Miki Sudo	41	United States
40	2018	Joey Chestnut	74*	United States	Miki Sudo	37	United States
41	2019	Joey Chestnut	71	United States	Miki Sudo	31	United States
42							
43	Notes: * means new record						

# Strategy 1: divide & conquer

Steps:

1. Read in the data
2. Clean the names
3. Remove \* note at bottom of table

```
hot_dogs <- read_excel(  
  here::here('data', 'hot_dog_winners.xlsx'),  
  sheet = 'hot_dog_winners') %>%  
  clean_names() %>%  
  dplyr::filter(!is.na(mens))  
  
glimpse(hot_dogs)
```

```
#> Rows: 40  
#> Columns: 7  
#> $ year      <chr> "1980", "1981", "1982", "1983"  
#> $ mens      <chr> "Paul Siederman & Joe Baldini"  
#> $ dogs_eaten_3 <chr> "9.1", "11", "11", "19.5", "9"  
#> $ country_4  <chr> "United States", "United States"  
#> $ womens    <chr> NA, NA, NA, NA, NA, NA, NA, NA  
#> $ dogs_eaten_6 <chr> NA, NA, NA, NA, NA, NA, NA, NA  
#> $ country_7  <chr> NA, NA, NA, NA, NA, NA, NA, NA
```

# Strategy 1: divide & conquer

## Steps

1. Read in the data
2. Clean the names
3. Remove \* note at bottom of table
4. **Split data into two competitions with the same variable names**
5. **Create new variable in each data frame: `competition`**

```
hot_dogs_m <- hot_dogs %>%
  select(
    year,
    competitor = mens,
    dogs_eaten = dogs_eaten_3,
    country    = country_4) %>%
  mutate(competition = 'Mens')

hot_dogs_w <- hot_dogs %>%
  select(
    year,
    competitor = womens,
    dogs_eaten = dogs_eaten_6,
    country    = country_7) %>%
  mutate(competition = 'Womens') %>%
  dplyr::filter(!is.na(competitor))
```

# Strategy 1: divide & conquer

## Steps

1. Read in the data
2. Clean the names
3. Remove \* note at bottom of table
4. Split data into two competitions with the same variable names
5. Create new variable in each data frame: `competition`
6. **Merge data together with `bind_rows()`**
7. **Clean up final data frame**

```
hot_dogs <- bind_rows(hot_dogs_m, hot_dogs_w) %>%  
  mutate(  
    new_record = str_detect(dogs_eaten, "\\*"),  
    dogs_eaten = parse_number(dogs_eaten),  
    year       = as.numeric(year))  
  
glimpse(hot_dogs)
```

```
#> Rows: 49  
#> Columns: 6  
#> $ year      <dbl> 1980, 1981, 1982, 1983, 1984,  
#> $ competitor <chr> "Paul Siederman & Joe Baldini"  
#> $ dogs_eaten <dbl> 9.10, 11.00, 11.00, 19.50, 9.5  
#> $ country    <chr> "United States", "United State  
#> $ competition <chr> "Mens", "Mens", "Mens", "Mens"  
#> $ new_record <lgl> FALSE, FALSE, FALSE, FALSE, FA
```

	A	B	C	D	E	F	G
1	Year	Mens	Dogs eaten	Country	Womens	Dogs eaten	Country
2	1980	Paul Siederman & Joe Baldini	9.1	United States			
3	1981	Thomas DeBerry	11	United States			
4	1982	Steven Abrams	11	United States			
5	1983	Luis Llamas	19.5	Mexico			
6	1984	Birgit Felden	9.5	Germany			
7	1985	Oscar Rodriguez	11.75	United States			
8	1986	Mark Heller	15.5	United States			
9	1987	Don Wolfman	12	United States			
10	1988	Jay Green	14	United States			
11	1989	Jay Green	13	United States			
12	1990	Mike DeVito	16	United States			
13	1991	Frank Dellarosa	21.5*	United States			
14	1992	Frank Dellarosa	19	United States			
15	1993	Mike DeVito	17	United States			
16	1994	Mike DeVito	20	United States			
17	1995	Edward Krachie	19.5	United States			
18	1996	Edward Krachie	22.25*	United States			
19	1997	Hirofumi Nakajima	24.5*	Japan			
20	1998	Hirofumi Nakajima	19	Japan			
21	1999	Steve Keiner	20.25	United States			
22	2000	Kazutoyo Arai	25.13*	Japan			
23	2001	Takeru Kobayashi	50*	Japan			
24	2002	Takeru Kobayashi	50.5*	Japan			
25	2003	Takeru Kobayashi	44.5	Japan			
26	2004	Takeru Kobayashi	53.5*	Japan			
27	2005	Takeru Kobayashi	49	Japan			
28	2006	Takeru Kobayashi	53.75*	Japan			
29	2007	Joey Chestnut	66*	United States			
30	2008	Joey Chestnut	59	United States			
31	2009	Joey Chestnut	68*	United States			
32	2010	Joey Chestnut	54	United States			
33	2011	Joey Chestnut	62	United States	Sonya Thomas	40*	United States
34	2012	Joey Chestnut	68	United States	Sonya Thomas	45*	United States
35	2013	Joey Chestnut	69*	United States	Sonya Thomas	36.75	United States
36	2014	Joey Chestnut	61	United States	Miki Sudo	34	United States
37	2015	Matt Stonie	62	United States	Miki Sudo	38	United States
38	2016	Joey Chestnut	70*	United States	Miki Sudo	38.5	United States
39	2017	Joey Chestnut	72*	United States	Miki Sudo	41	United States
40	2018	Joey Chestnut	74*	United States	Miki Sudo	37	United States
41	2019	Joey Chestnut	71	United States	Miki Sudo	31	United States
42							
43	Notes: * means new record						

```
head(hot_dogs)
```

```
#> # A tibble: 6 x 6
#>   year competitor dogs_eaten country competitor
#>   <dbl> <chr>      <dbl> <chr>      <chr>
#> 1 1980 Paul Siederman & Joe Baldini 9.1 United States Mens
#> 2 1981 Thomas DeBerry 11 United States Mens
#> 3 1982 Steven Abrams 11 United States Mens
#> 4 1983 Luis Llamas 19.5 Mexico Mens
#> 5 1984 Birgit Felden 9.5 Germany Mens
#> 6 1985 Oscar Rodriguez 11.8 United States Mens
```

# Strategy 2: gather, separate, spread

Steps:

1. Read in the data
2. Clean the names
3. Remove \* note at bottom of table

```
hot_dogs <- read_excel(  
  here::here('data', 'hot_dog_winners.xlsx'),  
  sheet = 'hot_dog_winners') %>%  
  clean_names() %>%  
  dplyr::filter(!is.na(mens))  
  
glimpse(hot_dogs)
```

```
#> Rows: 40  
#> Columns: 7  
#> $ year      <chr> "1980", "1981", "1982", "1983"  
#> $ mens      <chr> "Paul Siederman & Joe Baldini"  
#> $ dogs_eaten_3 <chr> "9.1", "11", "11", "19.5", "9"  
#> $ country_4  <chr> "United States", "United States"  
#> $ womens    <chr> NA, NA, NA, NA, NA, NA, NA, NA  
#> $ dogs_eaten_6 <chr> NA, NA, NA, NA, NA, NA, NA, NA  
#> $ country_7  <chr> NA, NA, NA, NA, NA, NA, NA, NA
```

# Strategy 2: gather, separate, spread

Steps:

1. Read in the data
2. Clean the names
3. Remove \* note at bottom of table
4. **Rename variables**
5. **Gather all the "joint" variables**

```
hot_dogs <- hot_dogs %>%
  select(
    year,
    competitor.mens = mens,
    competitor.womens = womens,
    dogs_eaten.mens = dogs_eaten_3,
    dogs_eaten.womens = dogs_eaten_6,
    country.mens = country_4,
    country.womens = country_7) %>%
  gather(key = 'variable', value = 'value',
         competitor.mens:country.womens)

head(hot_dogs, 3)
```

```
#> # A tibble: 3 x 3
#>   year variable      value
#>   <chr> <chr>      <chr>
#> 1 1980 competitor.mens Paul Siederman & Joe Baldi
#> 2 1981 competitor.mens Thomas DeBerry
#> 3 1982 competitor.mens Steven Abrams
```



# Strategy 2: gather, separate, spread

Steps:

1. Read in the data
2. Clean the names
3. Remove \* note at bottom of table
4. Rename variables
5. Gather all the "joint" variables
6. **Separate "joint" variables into components**

```
hot_dogs <- hot_dogs %>%  
  separate(variable, into = c('variable', 'competition'),  
           sep = '\\.')
```

```
head(hot_dogs)
```

```
#> # A tibble: 6 x 4  
#>   year variable competition value  
#>   <chr> <chr>      <chr>      <chr>  
#> 1 1980 competitor mens      Paul Siederman & Joe Baldini  
#> 2 1981 competitor mens      Thomas DeBerry  
#> 3 1982 competitor mens      Steven Abrams  
#> 4 1983 competitor mens      Luis Llamas  
#> 5 1984 competitor mens      Birgit Felden  
#> 6 1985 competitor mens      Oscar Rodriguez
```

# Strategy 2: gather, separate, spread

Steps:

1. Read in the data
2. Clean the names
3. Remove \* note at bottom of table
4. Rename variables
5. Gather all the "joint" variables
6. Separate "joint" variables into components
7. **Spread variable and value back to columns**

```
hot_dogs <- hot_dogs %>%  
  spread(key = variable, value = value) %>%  
  mutate(  
    new_record = str_detect(dogs_eaten, "\\*"),  
    dogs_eaten = parse_number(dogs_eaten),  
    year       = as.numeric(year))  
  
glimpse(hot_dogs)
```

```
#> Rows: 80  
#> Columns: 6  
#> $ year      <dbl> 1980, 1980, 1981, 1981, 1982, 1982, 198  
#> $ competition <chr> "mens", "womens", "mens", "womens", "me  
#> $ competitor  <chr> "Paul Siederman & Joe Baldini", NA, "Th  
#> $ country     <chr> "United States", NA, "United States", N  
#> $ dogs_eaten  <dbl> 9.10, NA, 11.00, NA, 11.00, NA, 19.50,  
#> $ new_record  <lgl> FALSE, NA, FALSE, NA, FALSE, NA, FALSE,
```

## Divide & conquer

```
hot_dogs <- read_excel(
  here::here('data', 'hot_dog_winners.xlsx'),
  sheet = 'hot_dog_winners') %>%
  clean_names() %>%
  dplyr::filter(!is.na(mens))
```

### # Divide

```
hot_dogs_m <- hot_dogs %>%
  select(
    year,
    competitor = mens,
    dogs_eaten = dogs_eaten_3,
    country = country_4) %>%
  mutate(competition = 'Mens')
hot_dogs_w <- hot_dogs %>%
  select(
    year,
    competitor = womens,
    dogs_eaten = dogs_eaten_6,
    country = country_7) %>%
  mutate(competition = 'Womens') %>%
  dplyr::filter(!is.na(competitor))
```

### # Merge and finish cleaning

```
hot_dogs <- bind_rows(hot_dogs_m, hot_dogs_w) %>%
  mutate(
    new_record = str_detect(dogs_eaten, "\\*"),
    dogs_eaten = parse_number(dogs_eaten),
    year = as.numeric(year))
```

## Gather, separate, spread

```
hot_dogs <- read_excel(
  here::here('data', 'hot_dog_winners.xlsx'),
  sheet = 'hot_dog_winners') %>%
  clean_names() %>%
  dplyr::filter(!is.na(mens)) %>%
```

### # Rename variables

```
select(
  year,
  competitor.mens = mens,
  competitor.womens = womens,
  dogs_eaten.mens = dogs_eaten_3,
  dogs_eaten.womens = dogs_eaten_6,
  country.mens = country_4,
  country.womens = country_7) %>%
```

### # Gather "joint" variables

```
gather(key = 'variable', value = 'value',
       competitor.mens:country.womens) %>%
```

### # Separate "joint" variables

```
separate(variable, into = c('variable', 'competition'),
         sep = '\\.') %>%
```

### # Spread "joint" variables

```
spread(key = variable, value = value) %>%
```


### # Finish cleaning

```
mutate(
  new_record = str_detect(dogs_eaten, "\\*"),
  dogs_eaten = parse_number(dogs_eaten),
  year = as.numeric(year))
```

# Strategies for dealing with sub-headers

Example:

OICA passenger car sales data

	A	E	F	G	H	I	J	K	L	M	N	O	P	Q	R
1		<b>NEW PC REGISTRATIONS OR SALES</b>													
2															
3															
4															
5		<i>Estimated figures</i>													
6	REGIONS/COUNTRIES	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018
7															
8	<b>EUROPE</b>	<b>17,906,455</b>	<b>18,685,556</b>	<b>19,618,588</b>	<b>18,821,599</b>	<b>16,608,761</b>	<b>16,499,863</b>	<b>17,167,600</b>	<b>16,191,269</b>	<b>15,942,273</b>	<b>16,154,279</b>	<b>16,410,563</b>	<b>17,291,819</b>	<b>17,974,281</b>	<b>17,912,336</b>
9	<b>EU 28 countries + EFTA</b>	<b>15,622,035</b>	<b>15,961,138</b>	<b>16,147,274</b>	<b>14,911,880</b>	<b>14,533,115</b>	<b>13,830,694</b>	<b>13,642,659</b>	<b>12,567,903</b>	<b>12,344,415</b>	<b>13,061,461</b>	<b>14,287,881</b>	<b>15,160,239</b>	<b>15,631,283</b>	<b>15,626,509</b>
10	<b>EU 15 countries + EFTA</b>	<b>14,565,695</b>	<b>14,820,182</b>	<b>14,842,186</b>	<b>13,602,038</b>	<b>13,668,808</b>	<b>12,984,549</b>	<b>12,815,435</b>	<b>11,773,281</b>	<b>11,555,153</b>	<b>12,148,648</b>	<b>13,261,258</b>	<b>13,971,468</b>	<b>14,320,223</b>	<b>14,210,016</b>
11	AUSTRIA	307,915	308,594	298,182	293,697	319,403	328,563	356,145	336,010	319,035	303,318	308,555	329,604	353,320	341,068
12	BELGIUM	480,088	526,141	524,795	535,947	476,194	547,340	572,211	486,737	486,065	482,939	501,066	539,519	546,558	549,632
13	DENMARK	148,819	156,936	162,686	150,199	112,454	153,858	170,036	170,763	182,086	189,055	207,717	222,924	221,821	218,566
14	FINLAND	148,161	145,700	125,608	139,669	90,574	111,968	126,123	111,251	103,455	106,237	108,819	118,991	120,480	120,480
15	FRANCE	2,118,042	2,045,745	2,109,672	2,091,369	2,302,398	2,251,669	2,204,229	1,898,760	1,790,456	1,795,885	1,917,226	2,015,177	2,110,748	2,173,481
16	GERMANY	3,319,259	3,467,961	3,148,163	3,090,040	3,807,175	2,916,259	3,173,634	3,082,504	2,952,431	3,036,773	3,206,042	3,351,607	3,441,262	3,435,778
17	GREECE	269,728	267,669	279,745	267,295	219,730	141,501	97,680	58,482	58,694	71,218	75,805	78,873	88,083	103,431
18	ICELAND	18,060	17,129	15,942	9,033	2,113	3,106	5,038	7,902	7,274	9,537	14,004	18,442	21,324	17,976
19	IRELAND	171,742	178,484	186,325	151,607	57,453	88,446	89,911	79,498	74,367	96,284	124,804	146,600	131,332	125,557
20	ITALY	2,244,108	2,335,462	2,494,115	2,161,359	2,159,465	1,961,580	1,749,740	1,403,010	1,304,648	1,360,578	1,575,737	1,824,968	1,970,497	1,910,025
21	LUXEMBOURG	48,517	50,837	51,332	52,359	47,265	49,726	49,881	50,398	46,624	49,793	46,473	50,561	52,775	52,786
22	NETHERLANDS	465,196	483,999	504,300	499,980	387,699	482,531	555,812	502,454	417,036	387,553	449,350	382,825	414,306	443,531
23	NORWAY	109,907	109,164	129,195	110,617	98,675	127,754	138,345	137,967	142,151	144,202	150,686	154,603	158,650	147,929
24	PORTUGAL	206,488	194,702	201,816	213,389	161,013	223,464	153,404	95,309	105,921	142,826	178,503	207,345	222,129	228,327
25	SPAIN	1,528,877	1,634,608	1,614,835	1,161,176	952,772	982,015	808,051	699,589	722,689	890,125	1,094,077	1,147,007	1,234,932	1,321,438
26	SWEDEN	274,301	282,766	306,794	253,982	213,408	289,684	304,984	279,899	269,599	303,948	345,108	372,318	379,393	353,729
27	SWITZERLAND (HFL)	266,770	269,421	284,674	288,525	266,018	294,239	318,958	328,139	307,885	301,942	323,783	317,318	311,996	299,135
28	UNITED KINGDOM	2,439,717	2,344,864	2,404,007	2,131,795	1,994,999	2,030,846	1,941,253	2,044,609	2,264,737	2,476,435	2,633,503	2,692,786	2,540,617	2,367,147
29	<b>EUROPE NEW MEMBERS</b>	<b>1,056,340</b>	<b>1,140,956</b>	<b>1,305,088</b>	<b>1,309,842</b>	<b>864,307</b>	<b>846,145</b>	<b>827,224</b>	<b>794,622</b>	<b>789,262</b>	<b>912,813</b>	<b>1,026,623</b>	<b>1,188,771</b>	<b>1,311,060</b>	<b>1,416,493</b>
30	BULGARIA*	25,956	36,455	43,521	45,143	22,869	16,257	19,250	19,419	19,352	20,359	23,500	26,370	33,265	37,506
31	CROATIA	70,541	78,775	82,664	88,265	44,918	38,587	41,561	31,360	27,802	33,962	35,715	44,106	50,769	60,041
32	CYPRUS	17,687	18,639	22,878	22,241	14,981	14,088	13,480	10,123	7,102	8,276	10,344	12,643	13,127	13,135
33	CZECH REPUBLIC	151,699	156,686	174,456	182,554	167,708	169,580	173,595	174,009	164,736	192,314	230,857	259,693	271,595	261,437
34	ESTONIA	19,640	25,363	30,912	24,579	9,946	10,295	17,070	19,424	20,969	20,969	20,347	22,429	25,618	26,297
35	HUNGARY	198,982	187,676	171,661	153,278	60,189	43,476	45,094	53,059	56,139	67,476	77,171	96,552	116,265	136,601
36	LATVIA	10,467	14,234	21,606	22,217	7,515	7,970	13,234	10,665	10,636	12,452	13,765	16,359	16,698	16,878
37	LITHUANIA	16,602	25,582	32,771	19,831	5,367	6,365	10,980	12,165	12,163	14,503	17,085	20,320	25,836	32,382
38	MALTA	6,552	6,745	6,240	5,423	5,894	4,056	5,428	5,884	5,749	6,451	7,121	7,333	7,825	8,128
39	POLAND	207,007	224,728	277,427	319,190	276,220	315,855	277,427	272,719	289,913	327,709	354,975	416,123	486,352	531,889
40	ROMANIA	214,967	247,411	312,533	285,506	116,016	94,441	81,709	66,436	57,710	82,809	98,325	115,004	105,083	129,004
41	SLOVAKIA	56,916	59,084	59,700	70,040	74,717	64,033	68,203	69,268	65,998	72,237	77,968	88,165	96,105	98,080
42	SLOVENIA	59,324	59,578	68,719	71,575	57,967	61,142	60,193	50,091	52,268	53,296	59,450	68,674	62,522	65,115
43	<b>RUSSIA, TURKEY &amp; OTHER EUROPE</b>	<b>2,284,420</b>	<b>2,724,418</b>	<b>3,471,314</b>	<b>3,909,719</b>	<b>2,075,646</b>	<b>2,669,169</b>	<b>3,524,941</b>	<b>3,623,366</b>	<b>3,597,858</b>	<b>3,092,818</b>	<b>2,122,682</b>	<b>2,131,580</b>	<b>2,342,998</b>	<b>2,285,827</b>

# Strategies for dealing with sub-headers

Steps:

1. Read in the data, skipping first 5 rows
2. Clean the names

```
pc_sales <- read_excel(  
  here::here('data', 'pc_sales_2018.xlsx'),  
  sheet = 'pc_sales', skip = 5) %>%  
  clean_names() %>%  
  rename(country = regions_countries)  
  
glimpse(pc_sales)
```

```
#> Rows: 160  
#> Columns: 18  
#> $ country <chr> NA, "EUROPE", "EU 28 countries + E  
#> $ x2 <lgl> NA, NA, NA, NA, NA, NA, NA, NA, NA  
#> $ x3 <lgl> NA, NA, NA, NA, NA, NA, NA, NA, NA  
#> $ x4 <lgl> NA, NA, NA, NA, NA, NA, NA, NA, NA  
#> $ x2005 <dbl> NA, 17906455, 15622035, 14565695,  
#> $ x2006 <dbl> NA, 18685556, 15961138, 14820182,  
#> $ x2007 <dbl> NA, 19618588, 16147274, 14842186,  
#> $ x2008 <dbl> NA, 18821599, 14911880, 13602038,  
#> $ x2009 <dbl> NA, 16608761, 14533115, 13668808,  
#> $ x2010 <dbl> NA, 16499863, 13830694, 12984549,  
#> $ x2011 <dbl> NA, 17167600, 13642659, 12815435,
```

# Strategies for dealing with sub-headers

Steps:

1. Read in the data, skipping first 5 rows
2. Clean the names
3. **Drop bad columns**
4. **Filter out bad rows**

Use **datapasta** to get rows to drop

```
drop <- c(
  'EUROPE', 'EU 28 countries + EFTA',
  'EU 15 countries + EFTA', 'EUROPE NEW MEMBERS',
  'RUSSIA, TURKEY & OTHER EUROPE', 'AMERICA',
  'NAFTA', 'CENTRAL & SOUTH AMERICA',
  'ASIA/OCEANIA/MIDDLE EAST', 'AFRICA', 'ALL COUNTRIES')

pc_sales <- pc_sales %>%
  select(-c(x2:x4)) %>% # Drop bad columns
  filter(! country %in% drop, # Drop bad rows
         ! is.na(country))

head(pc_sales)
```

```
#> # A tibble: 6 x 15
#>   country    x2005    x2006    x2007    x2008    x2009    x2010
#>   <chr>      <dbl>    <dbl>    <dbl>    <dbl>    <dbl>    <dbl>
#> 1 AUSTRIA  307915  308594  298182  293697  319403  328563
#> 2 BELGIUM  480088  526141  524795  535947  476194  547340
#> 3 DENMARK  148819  156936  162686  150199  112454  153858
#> 4 FINLAND  148161  145700  125608  139669   90574  111968
```

# Strategies for dealing with sub-headers

Steps:

1. Read in the data, skipping first 5 rows
2. Clean the names
3. Drop bad columns
4. Filter out bad rows
5. **Gather the year variables**

```
pc_sales <- pc_sales %>%  
  gather(key = 'year', value = 'num_cars', x2005:x2018)  
  
head(pc_sales)
```

```
#> # A tibble: 6 x 3  
#>   country year  num_cars  
#>   <chr>   <chr>   <dbl>  
#> 1 AUSTRIA x2005    307915  
#> 2 BELGIUM x2005    480088  
#> 3 DENMARK x2005    148819  
#> 4 FINLAND x2005    148161  
#> 5 FRANCE  x2005    2118042  
#> 6 GERMANY x2005    3319259
```

# Strategies for dealing with sub-headers

Steps:

1. Read in the data, skipping first 5 rows
2. Clean the names
3. Drop bad columns
4. Filter out bad rows
5. Gather the year variables
6. **Separate the "x" from the year**

```
pc_sales <- pc_sales %>%  
  separate(year, into = c('drop', 'year'), sep = 'x',  
           convert = TRUE)  
head(pc_sales)
```

```
#> # A tibble: 6 x 4  
#>   country drop   year num_cars  
#>   <chr>   <lgl> <int>   <dbl>  
#> 1 AUSTRIA NA     2005   307915  
#> 2 BELGIUM NA     2005   480088  
#> 3 DENMARK NA     2005   148819  
#> 4 FINLAND NA     2005   148161  
#> 5 FRANCE  NA     2005  2118042  
#> 6 GERMANY NA     2005  3319259
```



# Strategies for dealing with sub-headers

Steps:

1. Read in the data, skipping first 5 rows
2. Clean the names
3. Drop bad columns
4. Filter out bad rows
5. Gather the year variables
6. Separate the "x" from the year
7. **Remove the drop column**
8. **Finish cleaning**

```
pc_sales <- pc_sales %>%  
  select(-drop) %>%  
  mutate(country = str_to_title(country))  
  
head(pc_sales)
```

```
#> # A tibble: 6 x 3  
#>   country  year num_cars  
#>   <chr>    <int>   <dbl>  
#> 1 Austria  2005   307915  
#> 2 Belgium  2005   480088  
#> 3 Denmark  2005   148819  
#> 4 Finland  2005   148161  
#> 5 France   2005  2118042  
#> 6 Germany  2005  3319259
```

# What if I wanted to keep the continents?

Strategy: Join a new data frame linking country -> continent

```

drop <- c(
  'EUROPE', 'EU 28 countries + EFTA',
  'EU 15 countries + EFTA', 'EUROPE NEW MEMBERS',
  'RUSSIA, TURKEY & OTHER EUROPE', 'AMERICA',
  'NAFTA', 'CENTRAL & SOUTH AMERICA',
  'ASIA/OCEANIA/MIDDLE EAST', 'AFRICA', 'ALL COUNTRIES')

pc_sales <- read_excel(
  here::here('data', 'pc_sales_2018.xlsx'),
  sheet = 'pc_sales', skip = 5) %>%
  clean_names() %>%
  rename(country = regions_countries) %>%
  select(-c(x2:x4)) %>% # Drop bad columns
  filter(! country %in% drop, # Drop bad rows
         ! is.na(country)) %>%
  gather(key = 'year', value = 'num_cars', x2005:x2018) %>%
  separate(year, into = c('drop', 'year'), sep = 'x',
           convert = TRUE) %>%
  select(-drop)

head(pc_sales, 3)

```

```

#> # A tibble: 3 x 3
#>   country year num_cars
#>   <chr>   <int>   <dbl>
#> 1 AUSTRIA  2005    307915
#> 2 BELGIUM  2005    480088
#> 3 DENMARK  2005    148819

```

# Strategy 1: Find another source

# Strategy 2: Hand-make it

```
pc_regions <- read_csv(here::here(
  "data", "pc_regions.csv"))
head(pc_regions)
```

```
#> # A tibble: 6 x 3
#>   country region subregion
#>   <chr>   <chr>   <chr>
#> 1 AUSTRIA EUROPE EU 15 countries + EFTA
#> 2 BELGIUM EUROPE EU 15 countries + EFTA
#> 3 DENMARK EUROPE EU 15 countries + EFTA
#> 4 FINLAND EUROPE EU 15 countries + EFTA
#> 5 FRANCE  EUROPE EU 15 countries + EFTA
#> 6 GERMANY EUROPE EU 15 countries + EFTA
```

```
pc_sales <- pc_sales %>%
  left_join(pc_regions)
head(pc_sales)
```

```
#> # A tibble: 6 x 5
#>   country year num_cars region subregion
#>   <chr>   <int>   <dbl> <chr>   <chr>
#> 1 AUSTRIA 2005   307915 EUROPE EU 15 cou
#> 2 BELGIUM 2005   480088 EUROPE EU 15 cou
#> 3 DENMARK 2005   148819 EUROPE EU 15 cou
#> 4 FINLAND 2005   148161 EUROPE EU 15 cou
#> 5 FRANCE  2005  2118042 EUROPE EU 15 cou
#> 6 GERMANY 2005  3319259 EUROPE EU 15 cou
```

	A	E	F	G	H	I	J	K	L	M	N	O	P	Q	R
1															
2															
3															
4															
5															
6															
7															
8															
9															
10															
11															
12															
13															
14															
15															
16															
17															
18															
19															
20															
21															
22															
23															
24															
25															
26															
27															
28															
29															
30															
31															
32															
33															
34															
35															
36															
37															
38															
39															
40															
41															
42															
43															

```
drop <- c(
  'EUROPE', 'EU 28 countries + EFTA',
  'EU 15 countries + EFTA', 'EUROPE NEW MEMBERS',
  'RUSSIA, TURKEY & OTHER EUROPE', 'AMERICA',
  'NAFTA', 'CENTRAL & SOUTH AMERICA',
  'ASIA/OCEANIA/MIDDLE EAST', 'AFRICA', 'ALL COUNTRIES')
```

```
pc_regions <- read_csv(here::here("data", "pc_regions.csv"))
```

```
pc_sales <- read_excel(
  here::here('data', 'pc_sales_2018.xlsx'),
  sheet = 'pc_sales', skip = 5) %>%
  clean_names() %>%
  rename(country = regions_countries) %>%
  select(-c(x2:x4)) %>% # Drop bad columns
  filter(! country %in% drop, # Drop bad rows
         ! is.na(country)) %>%
  gather(key = 'year', value = 'num_cars', x2005:x2018) %>%
  separate(year, into = c('drop', 'year'), sep = 'x',
           convert = TRUE) %>%
  select(-drop) %>%
  left_join(pc_regions) %>%
  mutate(
    country = str_to_title(country),
    region = str_to_title(region),
    subregion = str_to_title(subregion))
```

```
head(pc_sales)
```

```
#> # A tibble: 6 x 5
#>   country year num_cars region subregion
#>   <chr>   <int>   <dbl> <chr>   <chr>
#> 1 Austria  2005   307915 Europe Eu 15 Countries + Efta
#> 2 Belgium  2005   480088 Europe Eu 15 Countries + Efta
#> 3 Denmark  2005   148819 Europe Eu 15 Countries + Efta
#> 4 Finland  2005   148161 Europe Eu 15 Countries + Efta
#> 5 France   2005   2118042 Europe Eu 15 Countries + Efta
#> 6 Germany  2005   3319259 Europe Eu 15 Countries + Efta
```